



579.00 EUR  
incl. 19% VAT, plus [shipping](#)

- 12/22: New Model !
- JBC150F792-3160B !



- Intel® Braswell N3160 CPU
- 2\* DDR3L up to 8GB
- 1\* LPT, 1\* HDMI, 1\* VGA, 2\* COM
- Intel® Braswell N3160 Processor (TDP 6W)
- Support DDR3L-1600, 2 \* SO-DIMM slot, up to 8GB memory
- 3 \* USB2.0, 3 \* USB3.0, 1 \* HDMI, 1 \* VGA, 2 \* RJ45, 2 \* COM, 1 \* LPT, 1 \* MIC, 1 \* Line in, 1 \* Line out

|                |                                                                                                                                                                                                                                                                                                                                                |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model       | –JNF792-3160 / Mini ITX<br>–Core Number : Braswell N3160 (Default)                                                                                                                                                                                                                                                                             |
| Part No        | –HBJC150F792-3160R (non-WIFI)<br>–HBJC150F792W-3160R (WIFI)                                                                                                                                                                                                                                                                                    |
| BIOS           | –AMI 16MB SMT Flash ROM                                                                                                                                                                                                                                                                                                                        |
| CPU/Chipset    | –Intel® Braswell N3160 Processor (TDP 6W)                                                                                                                                                                                                                                                                                                      |
| Memory         | –2 * SO-DIMM slots DDR3L-1600MHz up to 8GB                                                                                                                                                                                                                                                                                                     |
| Storage        | –1 * 2.5" SATA3 6Gb/s internal drive bay<br>–1 * M.2 (M-key, 2242/2260)                                                                                                                                                                                                                                                                        |
| Network        | –2* REALTEK RTL81191GbE<br>–1 * full-size Mini-PCle slot (for WiFi expansion)                                                                                                                                                                                                                                                                  |
| Rear Panel I/O | –1 * Power, 1 * Reset SW<br>–1 * Power LED, 1 * HDD LED<br>–1 * USB2.0, 3 * USB3.0<br>–1 * HDMI (Max. resolution:3840×2160@30Hz)<br>–1 * VGA (Max. resolution:1920×1200@60Hz)<br>–1* LPT<br>–2 * RJ45<br>–1 * Line-in, 1 * Line-out, 1 * MIC<br>–2 * COM ports (COM1 supports RS232/422/485)<br>–2 * Antenna holes (Optional)<br>–1 * AC input |

|                 |                                                                                                                                                                                   |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Front Panel I/O | <ul style="list-style-type: none"> <li>-1 * Power button, 1 * Reset button</li> <li>-1 * Power LED, 1 * HDD LED</li> <li>-2 * USB2.0 ports</li> </ul>                             |
| Power Source    | -1U-250W / Support PFC / 150 (L) *81.5 (W) *40.5 (H) mm (FLEX)                                                                                                                    |
| FAN             | -4020 FAN * 3 / 7000 rpm / DC-12V-0.1A / 8 CFM                                                                                                                                    |
| Expansion       | -PCI-E x1 * 1                                                                                                                                                                     |
| Storage         | -3.5" HDD * 1 or 2.5" HDD * 2 (Support SATA 3)                                                                                                                                    |
| Accessory       | <ul style="list-style-type: none"> <li>-1 * Power Cord</li> <li>-1 * Quick Installation Guide</li> <li>-1 * User's Manual</li> <li>-1 * Screw Package</li> <li>-1 * CD</li> </ul> |
| Packing         | <ul style="list-style-type: none"> <li>-Net Weight: 3.5KG</li> <li>-Gross Weight: 4.5KG</li> <li>-Color Box dimension: 530 (W) * 352 (D) * 142 (H) mm</li> </ul>                  |
| Safety          | -CE , FCC , RoHS , REACH                                                                                                                                                          |
| Application     | -Automation                                                                                                                                                                       |