

539.00 EUR

incl. 19% VAT, plus [shipping](#)



- LGA1151 !
- H310 Chipset !
- 19" Enclosure !

- Intel® 8th & 9th Core i3/i5/i7/Pentium Processor
- Support 2* DDR4 2666 SO-DIMM up to 32 GB
- 4* USB3.1, 2* USB2.0, 2* COM, 1* HDMI , 1* DP, 2* RJ45, Line-out/Line-in/MIC
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

Dimensions	– 330 (W) x 192 (D) x 44 (H) mm		
MB model	– MI98-00 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm)		
Part No	Non-Wifi	Wifi	
	– HBJC150I98-H310-B	– HBJC150I98W-H310-B	
CPU	– Intel® 8/9th Core i3/i5/i7/Pentium/Celeron LGA Processor (TDP: 95W)		
BIOS	– AMI Flash ROM		
Memory	– 2* Dual CH non-ECC DDR4 2666 MHz SDRAM SO-DIMM up to 32GB		
Network	– 2* GbE (1*Intel i219V, 1* Realtek 8111H)		
Storage	– 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay – 1 *M.2_SSD (M key-2242/2280) support NVMe		
Expansion	– 1* M.2 E-key 2230 (PCIex1/USB2.0) – Support onboard TPM2.0 (MI98-02) / optional		
Rear I/O Port	– 4 * USB 3.1 (Gen. 1) – 1 * HDMI (Max Resolution: 4096×2160@30Hz) – 1 * DP (Max Resolution: 4096×2304@60Hz) – 2 * RJ45 (1*Intel i219V, 1* Realtek 8111H) – 1 * Mic , 1 * Line in , 1 * Line-out – 2 * COM (COM 1 support RS232/422/485) – AC-in		
Front I/O Port	– 1 * Power button – 1 * Reset button – 1 * Power LED – 1 * HDD LED – 2 * USB 2.0		
Power Source	– 1U 250W FLEX POWER – AC 90~240V input		

Certification	– CE, FCC, LVD, RoHS
Environment	– Operating Temperature : 0°C~50°C – Storage Temperature : -10°C~70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Packing	– Net Weight■3.5 KG – Gross Weight■4.5 KG – Color Box Dimension■560(W) x 400(D) x 140(H) mm