

999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel Gemini Lake-R !
- 2x LAN !
- 2x COM !

- Intel® Gemini Lake-R J4125 Soc Processor
- 1* DDR4 2400MHz SO-DIMM up to 8GB
- 1* M.2-2242 slot (M-key), 1* M.2-2230 slot (E-key)
- 2* HDMI, 1* DP
- 2* GbE, 3* USB 3.1(A-Type), 1* USB3.1(C-Type), 2* COM, 1* Audio
- DC12V/40W Adapter

Model	– HBJC420U11-4125B – HBJC420U11I-4125B (WIFI) – HBJC420U11-4125E (EMMC) – HBJC420U11I-4125E (WIFI/EMMC) – HBJC420U11-4125T (EMMC/TPM) – HBJC420U11I-4125T (WIFI/EMMC/TPM)
CPU/Chipset	– Intel® Gemini Lake J4125 2.0GHz Quad Core MCP processor (10W)
BIOS	– AMI Flash ROM
Memory	– 1* DDR4 2400MHz up to 8GB
Network	– 2* Realtek RTL8119I GbE
Graphics	– Intel® HD Graphics, shared memory – 1* DP (Max Resolution: 4096×2304@60Hz) – 2* HDMI 2.0 (Max Resolution: 4096×2160@60Hz) – Support Triple Displays
Storage	– 1* M.2 M-key (2242 W/ SATA interface)
Expansion	– M.2 E-Key (2230, CNVi/PCIe/USB2.0)
Rear Panel I/O	– 2* RJ45 – 2* USB3.1 (A Type) – 2* HDMI – 1* DP – 1* Audio combo – 1* DC-in Jack

Front Panel I/O	– 1* Power button/LED – 1* USB 3.1(A Type) – 1* USB 3.1(C Type) – 2* COM
Internal Connector	– 1* 32GB eMMC onboard option – TPM onboard option
Power Source	– MU11 MB : DC12V input – Adapter : AC 90~240V input / DC12V-40W output
Compliance	– CE, FCC, RoHS, ErP Ready
Temperature	– Operating Temperature: -20 ~ 50° C (Under the condition of using M.2 interface SSD)(The test environment is closed and windless) – Storage Temperature: -20 ~ 80° C – Humidity: Between 10% and 90%, @40° C (non-condensing)
Dimensions	– System: 129 (W) x 109.4 (D) x 34 (H) mm – Box: 158 (W) x 167 (D) x 123.6 (H) mm
OS Support	– Windows 10, Windows 11, Linux