



639.00 EUR

incl. 19% VAT, plus [shipping](#)

- LGA1200 !
- 2x LAN !
- 2x COM !

- Intel® LGA1200 Socket support 10th/11th Gen Core™ Processor
- Support 2* DDR4 3200/2933MHz SO-DIMM up to 64 GB
- 4* USB3.2 (Gen2), 2* USB3.2 (Gen1), 2* USB2.0, 2* COM, 1* HDMI , 1* DP, 1* VGA, 2* RJ45, 1* MIC, 1* Line out , Line in
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX 250W ATX Power
- Support TPM2.0 (option)

Model	– HBJC150LI22-H420B (non-Wifi) – HBJC150LI22I-H420B (M.2 ac Wifi)	
CPU/Chipset	– Intel® 10th/11th LGA 1200 Socket Core i7/i5/i3/Pentium/Celeron Processor(Max. 65W TDP)	
BIOS	– AMI Flash ROM	
Memory	– 2* DDR4 3200/2933MHz SDRAM SO-DIMM up to 64GB	
Network	– 1* Intel i219-LM GbE – 1* Intel i226-V 2.5GbE	
Graphics	– Intel® HD Graphics, shared memory, Support Dual Displays – 1* VGA (Max Resolution: 1920×1080@60Hz) – 1* HDMI 1.4 (Max Resolution: 4096×2160@30Hz) – 1* DP1.4 (Max Resolution: 5120×3200@60Hz) – Support Dual Display	
Storage	– 2* 2.5" SATA Device – 1* M.2 M-key (2242/2280, PCIe x4 interface) support NVMe SSD	
Expansion	– 1* M.2 E-key (2230, PCIe x1/USB2.0 interface) support CNVi for Wifi/BT – 1* PCIe x16 slot	

Rear Panel I/O	– 2* RJ45 – 1* DP – 1* HDMI – 1* VGA – 2* COM (RS232/422/485) – 4* USB3.2 (Gen.2) – 2* USB3.2 (Gen.1) – 1* Line-in, 1* Line-out, 1* MIC
Front Panel I/O	– 1* Power button, 1* Reset button – 1* Power LED, 1* HDD LED – 2* USB2.0
Internal Connector	– N.A
Power Source	– 1U FLEX 250W ATX POWER – AC 90~240V input
Compliance	– CE, FCC, RoHS, ErP Ready
Dimensions	– System: 430 (W) x 252 (D) x 44 (H) mm – Color Box dimension: 560 (W) x 400 (D) x 380 (H) mm
Temperature	– Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~70° C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	– Windows 11, Linux